



T-Flux Modular Spotlight

T-Flux modular spotlight installed via track mount or a ceiling recessed mounting disk. Designed with interchangeable optics for different beam angles and includes a media holder for lighting accessories i.e. filters, lens and honeycomb louvre. Complete with remote or in track driver. Built to conform to the requirements of BS EN 60598-1 and IEC 598. Photometrically tested to LM-79.



MODULAR COMPONENTS

The modular design makes it easy to change the specification or appearance to match the clients requirements. Also saves time and cost on maintenance.

Mounting



VERSATILE LED OUTPUT CONTROL

Various lumen output options depends on spotlight size. 2700K, 3000K, 4000K, Warm Dim, colour rendering $R_a > 90$ and 2 step Macadam are all available. Also provides wide range of control options such as Non-Dim, 0-10V, Dali, CASAMBI, TRIAC.



Driver Box Adaptor
Available Controls

- 0-10V
- Specific driver available by order



In-Track Driver Adaptor
Available Controls

- Non-Dim
- DALI
- CASAMBI
- TRIAC

CRI 98 COLOUR RENDERING OPTION IDEAL FOR GALLERY WORKS

For high end colour rendering such as galleries and luxury stores the T-Flux range can be supplied with Cree CRI98. The T-Flux 105 also has the option of using a Xicato light engine. With multiple options lighting designers can easily find the best solution for their projects.

BODY FINISHES

Available in white, black and bronze as standard, other colours available by order






Drawing Room, Tannery Arts
Lighting Designer: Tom Johnson, Sanford Lighting Design

LUMEN PACKAGE

T-Flux 55 Ø55mm

T-Flux 65 Ø65mm



T-Flux 55 & 65 both have a removable colour co-ordinated heatsink cover

T-Flux 55 - 19° / 22° / 35° / 47° Beam
CREE Lighting Engine - CRI 90, 2-Step MacAdam
2700K / 3000K / 4000K

Source Lumens	LED Wattage	Delivered Lumens	Efficacy	Delivered Lumens	Efficacy	Delivered Lumens	Efficacy	Delivered Lumens	Efficacy
		19°		22°		35°		47°	
900 lm	8.0 W	666 lm	83 lm/W	639 lm	79 lm/W	747 lm	93 lm/W	720 lm	90 lm/W
1100 lm	10.0 W	814 lm	81 lm/W	781 lm	78 lm/W	913 lm	91 lm/W	880 lm	88 lm/W
1250 lm	12.0 W	925 lm	77 lm/W	887 lm	73 lm/W	1037 lm	86 lm/W	1000 lm	83 lm/W

* Nominal delivered lumens

T-Flux 65 - 21° / 33° / 44° / 55° Beam
CREE Lighting Engine - CRI 90, 2-Step MacAdam
2700K / 3000K / 4000K

Source Lumens	LED Wattage	Delivered Lumens	Efficacy	Delivered Lumens	Efficacy	Delivered Lumens	Efficacy	Delivered Lumens	Efficacy
		21°		33°		44°		55°	
1500 lm	10.0 W	1100 lm	111 lm/W	1065 lm	106 lm/W	1245 lm	124 lm/W	1200 lm	120 lm/W
1730 lm	12.0 W	1280 lm	106 lm/W	1228 lm	102 lm/W	1435 lm	119 lm/W	1384 lm	115 lm/W
1950 lm	17.0 W	1443 lm	103 lm/W	1384 lm	98 lm/W	1618 lm	115 lm/W	1560 lm	111 lm/W

* Nominal delivered lumens

LUMEN PACKAGE

T-Flux 85 Ø85mm



T-Flux 105 Ø105mm



T-Flux 85 Standard - 19° / 25° / 36° / 50° Beam

CREE Lighting Engine - CRI 90, 2-Step MacAdam
2700K / 3000K / 4000K

Source Lumens	LED Wattage	Delivered Lumens	Efficacy	Delivered Lumens	Efficacy	Delivered Lumens	Efficacy	Delivered Lumens	Efficacy
		19°		25°		36°		50°	
1500 lm	10.0 W	1155 lm	115 lm/W	1260 lm	126 lm/W	1230 lm	123 lm/W	1200 lm	120 lm/W
1950 lm	14.0 W	1501 lm	107 lm/W	1638 lm	117 lm/W	1599 lm	114 lm/W	1560 lm	111 lm/W
2350 lm	17.0 W	1832 lm	107 lm/W	1999 lm	117 lm/W	1951 lm	114 lm/W	1904 lm	112 lm/W

* Nominal delivered lumens

T-Flux 105 Standard - 13° / 19° / 25° / 36° / 50° Beam

CREE Lighting Engine - CRI 90, 2-Step MacAdam
2700K / 3000K / 4000K

Source Lumens	LED Wattage	Delivered Lumens	Efficacy	Delivered Lumens	Efficacy	Delivered Lumens	Efficacy	Delivered Lumens	Efficacy	Delivered Lumens	Efficacy
		13°		19°		25°		36°		50°	
2380 lm	17.0 W	1880 lm	110 lm/W	1832 lm	107 lm/W	1999 lm	117 lm/W	1951 lm	114 lm/W	1904 lm	112 lm/W
2780 lm	21.0 W	2196 lm	104 lm/W	2140 lm	101 lm/W	2335 lm	111 lm/W	2279 lm	108 lm/W	2224 lm	105 lm/W
3160 lm	25.0 W	2496 lm	99 lm/W	2433 lm	97 lm/W	2654 lm	106 lm/W	2591 lm	103 lm/W	2528 lm	101 lm/W

* Nominal delivered lumens

T-FLUX 85 & T-FLUX 105

GALLERY VERSION LUMEN PACKAGE

T-Flux 85 Gallery - 19° / 25° / 36° / 50° Beam
CREE Lighting Engine - CRI 98, 2-Step MacAdam
2700K / 3000K / 4000K

Source Lumens	LED Wattage	Delivered Lumens	Efficacy	Delivered Lumens	Efficacy	Delivered Lumens	Efficacy	Delivered Lumens	Efficacy
		19°		25°		36°		50°	
1450 lm	10.0 W	1116 lm	111 lm/W	1218 lm	121 lm/W	1189 lm	118 lm/W	1160 lm	116 lm/W
1880 lm	14.0 W	1447 lm	103 lm/W	1579 lm	112 lm/W	1541 lm	110 lm/W	1504 lm	107 lm/W
2300 lm	17.0 W	1771 lm	104 lm/W	1932 lm	113 lm/W	1886 lm	110 lm/W	1840 lm	108 lm/W

* Nominal delivered lumens

T-Flux 105 Gallery - 13° / 19° / 25° / 36° / 50° Beam
CREE Lighting Engine - CRI 98, 2-Step MacAdam
2700K / 3000K / 4000K

Source Lumens	LED Wattage	Delivered Lumens	Efficacy	Delivered Lumens	Efficacy	Delivered Lumens	Efficacy	Delivered Lumens	Efficacy	Delivered Lumens	Efficacy
		13°		19°		25°		36°		50°	
2300 lm	17.0 W	1817 lm	106 lm/W	1771 lm	104 lm/W	1932 lm	113 lm/W	1886 lm	110 lm/W	1840 lm	108 lm/W
2680 lm	21.0 W	2117 lm	100 lm/W	2063 lm	98 lm/W	2251 lm	107 lm/W	2197 lm	104 lm/W	2144 lm	102 lm/W
3050 lm	25.0 W	2409 lm	96 lm/W	2348 lm	93 lm/W	2562 lm	102 lm/W	2501 lm	100 lm/W	2440 lm	97 lm/W


* Nominal delivered lumens

T-Flux 105 Gallery - 24° / 42° / 67° Beam
XICATO Lighting Engine - CRI >95, 2-Step MacAdam
2700K / 3000K / 4000K


Source Lumens	LED Wattage	Delivered Lumens	Efficacy	Delivered Lumens	Efficacy	Delivered Lumens	Efficacy
		24°		42°		67°	
1580 lm	17.0 W	1248 lm	73 lm/W	1216 lm	71 lm/W	1327 lm	78 lm/W
2140 lm	25.0 W	1690 lm	67 lm/W	1647 lm	65 lm/W	1797 lm	71 lm/W
3000 lm	36.0 W	2370 lm	65 lm/W	2310 lm	64 lm/W	2520 lm	70 lm/W

* Nominal delivered lumens

T-FLUX 85 STANDARD PHOTOMETRIC DATA



T-FLUX 105 GALLERY PHOTOMETRIC DATA



PRODUCT CODING EXAMPLE: T3A4323J35R620

Size	Distribution	Reflector Colour	Initial Lumen	CRI	Colour Temp	Driver Protocol	Shape	Case Colour	IP	Accessories	
T2A Ø55mm	2 11°-20°	1 Specular	15 1500 lm	B Xicato	2 2700K	0 Non-Dim	R Round	3 Black	2 IP20	0 None	
T2B Ø65mm	3 21°-30°	Silver	19 1950 lm	Ra95	3 3000K	1 1-10V		4 White		1 Honeycomb	
T3A Ø85mm	4 31°-40°	2 Satin Silver	23 2350 lm	J Cree	5 4000K	2 0-10V		6 Bronze		2 Elliptical Film	
T4A Ø105mm	5 41°-50°	3 Black		Ra90		5 DALI				3 Frosted Lens	
	6 51°-60°	4 White		K Cree		7 TRIAC					
		6 Bronze		Ra98		8 Casambi					
T3A	4	3	23	J	3	5	R	6	2	0	

DAL LONDON STUDIO

UNDERWOOD WORKS, 6-14 UNDERWOOD STREET, LONDON, N1 7JQ

+44 (0)207 4903998

SALES@DAL-UK.COM

WWW.DAL-UK.COM



© 2024. Designed Architectural Lighting.
All rights reserved, all designs and photos are protected by copyright.